

Inomhusavlopp EN 1451	
Böj PP	stk
32 x 15°	20
32 x 30°	20
32 x 45°	20
32 x 90°	20
50 x 15°	10
50 x 30°	10
50 x 45°	10
50 x 75°	10
50 x 90°	10
50 x 90°SW	30
75 x 15°	25
75 x 30°	25
75 x 45°	20
75 x 90°	20
75 x 90°SW	14
110 x 15°	36
110 x 30°	33
110 x 45°	27
110 x 90°	20
110 x 90°SW	16
160 x 15°	11
160 x 30°	9
160 x 45°	8
160 x 90°	6

Inomhusavlopp EN 1451	
Böj, all muffad PP	stk
32 x 15°+	20
32 x 30°+	20
32 x 45°+	20
32 x 90°+	20
50 x 15°+	10
50 x 30°+	10
50 x 45°+	10
50 x 75°+	10
50 x 90°+	10
50 x 90°+SW	30
75 x 15°+	25
75 x 30°+	25
75 x 45°+	20
75 x 90°+	20
75 x 90°+SW	14
110 x 15°+	33
110 x 30°+	27
110 x 45°+	25
110 x 90°+	20
110 x 90°+SW	16
160 x 15°+	9
160 x 30°+	8
160 x 45°+	8
160 x 90°+	8

Inomhusavlopp EN 1451	
Grenrör PP	stk
32 x 32 x 45°	10
32 x 32 x 90°	10
50 x 50 x 45°	25
75 x 50 x 45°	35
75 x 50 x 90°SW	30
75 x 75 x 45°	30
75 x 75 x 90°	25
75 x 75 x 90°SW	25
110 x 50 x 45°	15
110 x 50 x 90°	18
110 x 75 x 45°	15
110 x 75 x 90°	15
110 x 75 x 90°SW	10
110 x 110 x 45°	12
110 x 110 x 90°	10
110 x 110 x 90°SW	10
110 x 110 x 50 x 90°	7
110 x 110 x 75 x 90°	7
110 x 110 x 110 x 90°	7
110 x 110 x 110 x 45 / 90°SW	7
160 x 75 x 45°	5
160 x 110 x 45°	5
160 x 160 x 45°	4

Inomhusavlopp EN 1451	
Grenrör+, allmuffad PP	stk
32 x 32 x 45° +	10
32 x 32 x 90°+	10
50 x 50 x 45+	25
75 x 50 x 45+	35
75 x 50 x 90°+SW	30
75 x 75 x 45°+	30
75 x 75 x 90°+	25
75 x 75 x 90°+SW	25
110 x 50 x 45°+	15
110 x 50 x 90°+	18
110 x 75 x 45°+	15
110 x 75 x 90°+	15
110 x 75 x 90°+SW	10
110 x 110 x 45°+	12
110 x 110 x 90°+	10
110 x 110 x 90°+SW	10
110 x 110 x 50 x 90°+	7
110 x 110 x 75 x 90°+	7
110 x 110 x 110 x 90°+	7
110 x 110 x 110 x 45 / 90°+SW	7
160 x 110 x 45°+	5
160 x 160 x 45°+	4

Inomhusavlopp EN 1451	
Skjutmuff PP	stk
32	20
50	10
75	54
110	36
160	12

Dubbelmuff PP	
32+	20
50+	10
75+	36
110+	36
160+	12

Rör med muff PP	
32 x 1,8 x 3000	12
50 x 1,8 x 3000	50
75 x 2,3 x 3000	50
110 x 3,8 x 3000...6000	50
160 x 5,8 x 6000	28

Inomhusavlopp EN 1451	
Förminskning PP	stk
75 - 32	10
75 - 50	25
110 - 50	20
110 - 75	20
110 - 75	30
160 - 110	25

Propp PP	
75	120
110	42
160	15
200	30

SW = svängt

Standard färg:

32 / 50 / 75 / 110 mm = vit

50 / 75 / 110 mm = grå

160 / 200 mm = rödbrun

